

# **ATS** THERMOSTREAM<sup>®</sup> SYSTEMS

PRECISION TEMPERATURE SOURCES

the **BEST** at high speed thermal test





MORE FEATURES

PROVEN ERGONOMICS BROADER APPLICATIONS

# The ATS THERMOSTREAM® Systems

The ATS THERMOSTREAM® Systems are used in a variety of temperature testing and conditioning applications. From their traditional applications in semiconductor testing, failure analysis, and device characterization to their broader use in PCB and electronic sub-assembly testing, the ATS Series has a system with the temperature capabilities to meet your needs. The ATS THERMOSTREAM® Systems offer an innovative temperature testing solution that allows you to perform device, board, and module testing right where you need it – at your test bench, in your production facility, or in your lab. inTEST Thermal Solutions is the thermal expert with over 50 years of thermal engineering and test system development. Our goal is to make your temperature testing and conditioning as simple and cost effective as possible. The speed, precision, and portability of our new systems combined with a broader temperature range and capacity have resulted in the most comprehensive line of Temperature Forcing Systems ever – the ATS Series THERMOSTREAM®.





## **Features**

- · LN2 not required
- · Rapid temperature transitions of up to 18°C/sec
- 1.0°C accuracy
- · 0.1°C resolution
- · 50/60 Hz operation
- · 5 year compressor warranty

- · Ultimate high up to +300°C
- · Ultimate low down to -100°C
- · Extended reach for ease of use and optional extended height to accommodate all testheads
- · "Green" function to save power during idle periods
- · Heated defrost to quickly rid the system of moisture buildup

ATS - 700 SERIES THERMOSTREAM® Systems
The ATS-700 family consists of several high capacity THERMOSTREAM® Systems all designed to quickly and precisely take your devices and modules to temperature. With ultimate temperature capabilities from -100°C to +300°C, not only is it possible to improve your throughput by accelerating your time to temperature, you can now test high power devices and larger thermal mass subjects at or beyond MIL-STD temperatures in a 24/7 environment. Whether used in the conventional "articulated arm" configuration or as a temperature source for an external chamber or enclosure, the ATS-700 Series is both powerful and versatile.

"Improve throughput with systems capable of transition rates up to 18°C per second"

## MODEL

ATS - 710

ATS - 730

ATS - 750 ATS - 770 -80°C to +225°C

-90°C to +225°C high capacity

**TEMPERATURE RANGE** 

-90°C to +300°C high temp, high capacity

-100°C to +225°C ultra-low temp



The ATS 700 Series Models are available with a mechanical, articulated arm or a Turret for use with separate enclosures and chambers. Optionally, the mechanical arm can be equipped with an extended height feature.





## the **BEST** at innovative thermal solutions









inTEST Thermal Solutions, inTEST Corporation's group of thermal companies, is comprised of Temptronic, Sigma Systems and Thermonics Corporations. Combined, we have decades of engineering expertise forming a solutions center capable of solving all of your temperature testing and conditioning needs. We specialize in engineering unique thermal systems including semiconductor temperature test systems, custom thermal environments and platforms, ultra-low process chillers, temperature forcing systems, and everything in between. Rely on inTEST Thermal Solutions, where designing custom thermal solutions is standard practice.

## inTEST Thermal Solutions Worldwide Sales & Service

广东宏展科技有限公司

www.labcompanion.cn Tel: 400-628-2786

Email: info@labcompanion.cn

nTEST Thermal Solutions is a division of inTEST Corporation NASDAG: NTT) nTEST Corporate Headquarters 894 Eary Gore Drive 6 2012 inTEST Thermal Solutions THERMOSTREAMS is a registered insdeniet of Temptools Corporation. These specifications are said for stammer products only and are subject to change without notice. Applications requiring modifications of the mechanical thermal or electrical characteristics should be decorated with the factory for possible processing and entitle of the factory for possible processing and entitle or the factory.

document Part Number St.